

DROP - SIZE GUIDE ACCORDING TO CONDITIONS AND LENGTH

MODEL	MATERIAL	WEIGHT (KG)	5M 16'	6M 20'	7M 23'	8M 26'	9M 30'	10M 33'	11M 36'	12M 39'	13M 42'	14M 46'	15M 50'	16M 52'	17M 55'	18M 59'			
DP6ST	STAINLESS STEEL	6,5	Blue	Blue	Blue	Blue	Yellow	Yellow											
DP10ST	STAINLESS STEEL	10,2			Blue	Blue	Blue	Blue	Yellow	Yellow									
DP15ST	STAINLESS STEEL	14,8					Blue	Blue	Blue	Blue	Yellow	Yellow							
DP21ST	STAINLESS STEEL	21,7							Blue	Blue	Blue	Blue	Yellow						
DP26ST	STAINLESS STEEL	25,6									Blue	Blue	Blue	Blue	Yellow	Yellow			
DP35ST	STAINLESS STEEL	35,4										Blue	Blue	Blue	Blue	Yellow			
DP40ST	STAINLESS STEEL	40,5												Blue	Blue	Blue	Blue	Yellow	Yellow

 RECOMMENDED SIZE FOR MAIN ANCHOR IN GENERAL CONDITIONS ☀️ 🌊 🌬️
 RECOMMENDED SIZE AS FAIR-WEATHER ANCHOR OR SECONDARY ANCHOR USE ☀️

THIS GUIDE GIVES RECOMMENDATIONS FOR CHOOSING THE APPROPRIATE MODEL BASED ON THE WEATHER CONDITIONS AND THE LENGTH OF THE BOAT, CONSIDERING AN AVERAGE DISPLACEMENT, STRUCTURE EXPOSED TO THE WIND AND QUALITY OF THE SEA BOTTOM, AND PROCEEDING ACCORDING TO THE "INSTRUCTIONS FOR USE" PUBLISHED BY ANKERPLEX®. THESE RECOMMENDATIONS ARE BASED ON THE MANUFACTURER'S EXPERIENCE, FIELD TESTS CARRIED OUT AND SPECIALIZED PUBLICATIONS.

THERE MAY BE STANDARDS AND REGULATIONS IN YOUR COUNTRY THAT DETERMINE THE WEIGHT AND CHARACTERISTICS OF THE ANCHORING EQUIPMENT ON YOUR BOAT THAT MUST BE OBSERVED. PLEASE REMEMBER THAT THE CONDITIONS OF USE MAY VARY SIGNIFICANTLY IN THE PRESENCE OF CURRENTS, WAVES, ETC... LIKEWISE, THE HOLDING POWER OF AN ANCHOR CAN VARY CONSIDERABLY DEPENDING ON THE QUALITY OF THE BOTTOM.